



A-LineAcoustics.com

LS218A Powered Omni/Cardioid Selectable Subwoofer



Optimized for flat frequency response from 40-200Hz, the **LS218A** is the ideal subwoofer for natural live sound reproduction. Powered with proven **Bang & Olufsen ICEpower™** technology with onboard DSP the LS218A includes switchable omni/cardioid operation for better low frequency pattern control from 40-90Hz. Two high efficiency proprietary 18" drivers are loaded in separate, sealed chambers for maximum output. Low profile design with built-in tilt-back wheels make enclosures easily transportable and truck-pack friendly – 12 LS218A cabinets take up less than five linear feet stacked three high on optional wheel-boards and less than eight linear feet with 24 AL10 enclosures.(6 per wheel board)



Tilt-back wheels for easy maneuvering

Made in the USA with the highest grade components, A-Line enclosures are constructed in DuraTex coated birch plywood with integrated routed handles.

SPECIFICATIONS	LS218A Subwoofer
Power (Watts)	1000
Impedance	4 Ohms
Sensitivity	100dB
Max SPL	133dB
Freq. Resp.	40-200Hz
LF Drivers	2 x 18" Proprietary
Connectors	M&F XLR, I/O Powercon
HxWxD (in.)	44.5 x 21.8 x 22.8
Wt (lbs.)	160

Manufacturing and Distribution

510 East Washington Street, Corry, PA 16407 Tel. 814-663-0600 Fax. 814-664-7429

Marketing and Sales

4608 Cliff Drive Erie, PA 16511 Tel. 814 464-0631 mgorczycki@a-lineacoustics.com