



[A-LineAcoustics.com](http://A-LineAcoustics.com)

## uSoniq™ 112A & 112X Premium Powered and Un-powered Enclosures

These systems are the result of an exhaustive collaborative effort from top audio engineers and performing artists, employing advanced driver technology and design to deliver more powerful, higher quality audio to meet the needs of the most demanding performers. Constructed in birch plywood with integrated handles, enclosures are powered with **Bang & Olufsen ICEpower™** technology with onboard DSP and feature **B&C Neodymium** components **Made in the USA** with the highest quality components, uSoniq cabinets are also available with custom grilles and finishes for specified installation requirements.

**uSonic 112A** can be mirror imaged with a **uSonic 112X** to complete a Hybrid active system utilizing one amplifier to power one pair of speakers.



The speakers are mirrored with the stand mount pockets facing each other in the monitor position and a routed handle on the opposite end. This configuration allows for efficient stand mount of the speakers with the connecting NL4 cable connected behind the pole. Each amplifier has two DSP settings that can be selected by the user. Program one is equalized for half space operation for proper floor monitor use. Program two is equalized for full space operation for use on a speaker stand. Custom programs can be supplied for specific microphones or applications.

Model	uSonic 112A	uSonic 112X
<b>Configuration</b>	<b>2-way Powered</b>	<b>2-way Un-powered</b>
<b>Power (Watts)</b>	1,000	1,000
<b>Imp. LF/HF (ohms)</b>	8//16	8/16
<b>Sensitivity LF/HF</b>	98.5dB (1W/1m)/108(1W/1m)	98.5dB (1W/1m)/108(1W/1m)
<b>Max SPL</b>	130dB	130dB
<b>LF</b>	1 X 12 B&C Neodymium Woofer	1 X 12 B&C Neodymium Woofer
<b>HF</b>	Horn/ 1.4 B&C Neo Compression Driver	Horn 1.4 B&C Neo Compression Driver
<b>Horz. Dispersion</b>	60x80° Rotatable	60x80° Rotatable
<b>Amplifier</b>	B&O ICEPower–Dual Voltage w/DSP	N/A
<b>Connectors</b>	M&F XLR I/O, Powercon I/O /2NL4	2-NL4
<b>Power (Watts)</b>	500/125 RMS with uSonic 112X 1000/250	N/A
<b>x-over Freq.</b>	800Hz	800Hz
<b>Cabinet Configuration</b>	Monitor Mirrored with 112X / Stand Mount	Monitor Mirrored with 112A / Stand Mount
<b>HxWxD (in.)</b>	15.5x28.5.4x13.5	15.5x28.5.4x13.5
<b>Weight (lbs.)</b>	57.2 / 2.6	49.8 / 2.3

Specifications subject to change without notice

### *Manufacturing and Distribution*

510 East Washington Street, Corry, PA 16407 Tel. 814-663-0600 Fax. 814-664-7429

### *Marketing and Sales*

4608 Cliff Drive Erie, PA 16511 Tel. 814 464-0631 [mgorczycki@a-lineacoustics.com](mailto:mgorczycki@a-lineacoustics.com)